



Chain Sprocket Standard: DIN;ASA;ANSI;JIS;KANA or Chain Sprocket Made to Order;
 Induction Heating Chain Sprocket
 Chain Sprocket Processing Technic: Forged Forming
 Chain Sprocket Application:Using In All Transmission Equipment Together With Roller Chain
 1. Heat treatment: Harden teeth, tempering, queching
 2.Surface treatment: zinc plated, blacken, phopharization, carborized
 3. Process: Forging(casting)---lathe- teeth shaping---finishing---oil washing---Packing .
 4. Inspection: All items are checked and tested thoroughly during every working procedure and after the product is finally manufactured to ensure that the best quality product enter into the market.
 5. Durable, bad condition Resistance

Sprockets: 35 Sprockets



Motion(shanghai)Industrial Development Co.,Ltd

Brand	NO.OF TEETH	OUTSIDE DIAM.	PITCH DIAM.	BOTTOM OR CALIPER DIAM.	STOCK BORE	TYPE"B" SINGLE STRAND				WT. KG	MATERIAL	TYPE"A"		
	TEETH	OD	P.C.D			HUB DIAM.BD	HUB LENGTH BL THRU	BORE Min.	BORE Max.			STOCK	WT. KG	MATERIAL
VBF	10	163	143.84	118.44	26	98	56	28	66	4.9	SS418WTYPE(WELDINGWAY)S45C	28	2.9	SS41
VBF	11	178	157.78	130.77	26	106	56	28	70	5.5	-	28	3.6	-
VBF	12	193	171.74	146.34	26	117	56	28	80	6.6	-	28	4.2	-
VBF	13	207	185.74	158.98	26	117	63	28	80	7.9	-	28	4.9	-
VBF	14	221	199.76	174.36	26	127	63	28	89	9.3	-	28	5.7	-
VBF	15	236	312.79	187.22	26	127	63	28	89	10.1	-	28	6.6	-
VBF	16	250	227.84	202.44	26	127	63	28	89	11	-	28	7.5	-
VBF	17	264	241.91	215.47	26	127	63	28	89	12	-	28	8.4	-
VBF	18	279	255.98	230.58	26	127	63	28	89	13	-	28	9.4	-
VBF	19	293	270.06	243.74	26	137	71	28	95	15.6	-	28	10.5	-
VBF	20	307	284.15	258.75	26	137	71	28	95	16.7	-	28	11.6	-
VBF	21	322	298.24	272	26	137	71	28	95	17.9	-	28	12.8	-
VBF	22	336	312.34	286.94	26	137	71	28	95	18.4	-	28	14.1	-
VBF	23	350	326.44	300.28	26	137	71	28	95	20.1	-	28	15.3	-
VBF	24	364	340.54	315.14	26	137	71	28	95	20.9	-	28	16.7	-
VBF	25	379	354.65	328.56	26	147	80	28	103	24.1	-	28	18.1	-
VBF	26	393	368.77	343.37	26	147	80	28	103	25.5	-	28	19.6	-
VBF	27	407	382.88	356.83	26	147	80	28	103	28.2	-	28	-	-
VBF	28	421	397	371.6	26	147	80	28	103	30.1	-	28	-	-
VBF	30	450	425.24	399.84	26	147	80	28	103	31.5	-	28	26	-
VBF	32	478	453.49	428.09	26	147	80	28	103	36	-	28	29.7	-
VBF	35	521	495.88	369.98	26	157	90	28	110	42.9	-	28	35.6	-
VBF	36	535	510.05	484.61	26	157	90	28	110	47.4	-	28	37.6	-
VBF	38	563	538.27	512.87	26	157	90	28	110	51	-	28	41.9	-
VBF	40	591	566.54	541.14	26	157	90	28	110	53.1	-	28	46.4	-
VBF	42	620	594.81	569.41	26	157	90	28	110	60	-	28	51.1	-
VBF	45	662	637.22	611.43	26	167	100	28	118	68	-	28	58.8	-
VBF	48	705	679.63	654.23	26	167	100	28	118	75	-	28	66.9	-
VBF	50	733	707.47	682.51	26	167	100	28	118	85.3	-	28	72.5	-
VBF	54	790	764.47	739.07	26	167	100	28	118	97.4	-	28	84.6	-
VBF	60	875	849.32	823.92	26	167	112	28	118	119.3	-	28	104	-